


Product Definition	Dryback LVT		
Surface Treatment	UV, scratch-resistant coating		
Size	Planks: 1227 x 187mm	H'bone: 595 x 119mm	Tiles: 610 x 305mm
Panels Per Pack	16 Panels = 3.6712m ²	20 Panels = 1.4161m ²	16 Panels = 2.9728m ²
Embossing	EIR	EIR	Embossed
Thickness / Wear Layer	2.50mm / 0.55mm		
Micro-bevelled Edges		4 × micro-bevels per plank	
Performance Classification	EN ISO 10874	Class 33 / 42 Heavy Contract	
Residual Indentation	EN ISO 24343-1	≤0.1mm	
Reaction to Fire	EN 13501-1	Bfl-s1	
PTV	EN 16165:2021	36+ Wet & Dry	
Slip Resistance	DIN 51130	R10	
Resistance to Staining	ISO 26987	Pass	
Reaction to Light	ISO 105 B02	≥6	
Thermal Conductivity	EN 12667	0.051 m ² K/W	
Thermal Resistance	EN 12667	0.039 m ² K/W	
Acoustic impact noise reduction	EN ISO 10140	ΔL _w = 4 dB	
Dimensional Stability	EN ISO 23999	≤0.15%	
Curling Resultant to Heat	EN ISO 23999	≤1.0mm	
Underfloor Heating Suitability	Yes	Water based suitable	
Castor Chair Test	EN ISO 4918	Pass	
VOC Emissions	ISO 16000	A+	
Formaldehyde HCHO Emission	EN 717-1	Class E1	
Indoor Air Comfort	Certified		
UKCA / CE / Floorscore	Certified		
Wear Warranty	30 year residential / 15 year commercial		

For LRV (Light Reflective Values) please refer to www.hydroflooring.co.uk

